

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Graphite**

Print date: 20.05.2015

Product code: 128

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Graphite

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Uses advised against**

Reserved for industrial and professional use.

**1.3. Details of the supplier of the safety data sheet**

Company name:	ITW LLC & Co. KG	
Street:	Mühlackerstrasse 147	
Place:	D-75417 Mühlacker	
Telephone:	++49(0)7041-96340	Telefax: ++49(0)7041-963429
e-mail:	info@itwcp.de	
Internet:	www.itwcp.de	
Responsible Department:	Produktsicherheit	

**1.4. Emergency telephone number:** ++49(0)7041-96340  
Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Directive 67/548/EEC or 1999/45/EC**

Indications of danger: F+ - Extremely flammable, Xi - Irritant  
R phrases:  
Extremely flammable.  
Irritating to eyes.  
Repeated exposure may cause skin dryness or cracking.  
Vapours may cause drowsiness and dizziness.

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard categories:  
Flammable gas: Flam. Gas 1  
Hazard Statements:  
Extremely flammable aerosol.  
Pressurised container: May burst if heated.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

**2.2. Label elements**

**Hazardous components which must be listed on the label**  
n-butyl acetate, Acetone, Isopropanol

Signal word: Danger  
Pictograms: GHS02-GHS07

**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Graphite

Print date: 20.05.2015

Product code: 128

Page 2 of 8

H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

#### Precautionary statements

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P251 Do not pierce or burn, even after use.  
P271 Use only outdoors or in a well-ventilated area.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
204-658-1	n-butyl acetate	25-50%
123-86-4	R10-66-67	
607-025-00-1	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066	
200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	5-20%
67-63-0	F - Highly flammable, Xi - Irritant R11-36-67	
603-117-00-0	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
203-448-7	butane	10-25%
106-97-8	F+ - Extremely flammable R12	
601-004-00-0	Flam. Gas 1; H220	
200-827-9	propane	10-25%
74-98-6	F+ - Extremely flammable R12	
601-003-00-5	Flam. Gas 1; H220	

Full text of R-, H- and EUH-phrases: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

##### After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

##### After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

##### After ingestion

If swallowed, immediately drink: Water.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Graphite**

Print date: 20.05.2015

Product code: 128

Page 3 of 8

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO<sub>2</sub>). Foam. Extinguishing powder.**Unsuitable extinguishing media**

Water with tenside additive. Water.

**5.2. Special hazards arising from the substance or mixture**

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Explosion hazard.

**6.3. Methods and material for containment and cleaning up**

Ventilate affected area.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

Keep away from sources of ignition. - No smoking.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition.  
- No smoking.**Advice on storage compatibility**

Do not store together with: Material, rich in oxygen, oxidizing.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Graphite

Print date: 20.05.2015

Product code: 128

Page 4 of 8

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

#### 8.2. Exposure controls



##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

##### Eye/face protection

Tightly sealed safety glasses.

##### Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### Skin protection

Protective clothing:

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	black
Odour:	characteristic

#### Test method

##### Changes in the physical state

Initial boiling point and boiling range:	-0,5 °C
Flash point:	<0 °C
Lower explosion limits:	1,4 vol. %
Upper explosion limits:	9,4 vol. %
Ignition temperature:	365 °C
Vapour pressure: (at 20 °C)	2100 hPa

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Graphite**

Print date: 20.05.2015

Product code: 128

Page 5 of 8

Vapour pressure:  
(at 50 °C) 4900 hPaDensity (at 20 °C): 0,88 g/cm<sup>3</sup>**SECTION 10: Stability and reactivity****10.1. Reactivity**

No data available

**10.2. Chemical stability**

No data available

**10.3. Possibility of hazardous reactions**

No data available

**10.4. Conditions to avoid**

Keep away from heat. Ignition hazard.

**10.5. Incompatible materials**

No data available

**10.6. Hazardous decomposition products**

No data available

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
106-97-8	butane				
	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS

**Irritation and corrosivity**

Irritating to eyes. Vapours may cause drowsiness and dizziness.

**Severe effects after repeated or prolonged exposure**

Has degreasing effect on the skin. Frequently or prolonged contact with skin may cause dermal irritation.

**Additional information on tests**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**SECTION 12: Ecological information****12.3. Bioaccumulative potential****Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

**Further information**

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**SECTION 13: Disposal considerations**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Graphite**

Print date: 20.05.2015

Product code: 128

Page 6 of 8

**13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation.

**Waste disposal number of waste from residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing dangerous substances  
Classified as hazardous waste.

**Waste disposal number of contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 625  
Limited quantity: 1 L  
Transport category: 2  
Tunnel restriction code: D

**Other applicable information (land transport)**

E0

**Inland waterways transport (ADN)**

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L

**Other applicable information (inland waterways transport)**

E0

**Marine transport (IMDG)**

**14.1. UN number:** UN1950

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Graphite**

Print date: 20.05.2015

Product code: 128

Page 7 of 8

**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: See SP277  
EmS: F-D, S-U

**Other applicable information (marine transport)**

E0

**Air transport (ICAO)**

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
Hazard label: 2.1



Special Provisions: A145 A167  
Limited quantity Passenger: 30 kg G  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

**Other applicable information (air transport)**

E0

: Y203

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 16,67 % (146,696 g/l)

**National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

**SECTION 16: Other information****Relevant R-phrases (Number and full text)**

10 Flammable.  
11 Highly flammable.  
12 Extremely flammable.  
36 Irritating to eyes.  
66 Repeated exposure may cause skin dryness or cracking.  
67 Vapours may cause drowsiness and dizziness.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Graphite**

Print date: 20.05.2015

Product code: 128

Page 8 of 8

**Relevant H- and EUH-phrases (Number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*